Process Management

Lesson 03

Fall 2025 FI MU

Rado Vrbovsky <rvrbovsk@redhat.com>



- User Point of View
- Kernel Point of View
- Syscalls
- Process Scheduling



Process From User's Point of View

PID:

Code (Text)


Thread(s)

Heap


Stack

File Descriptors


Sockets



Process address space - Isolation



Process and kernel address space



Syscalls

```
#include <stdio.h>
int main(void) {
    printf("Hello World!\n");
    return 1;
}
```

```
hello:
      .ascii "Hello, World!\n"
hello len = . - hello
_start:
      mov $1, %rax
                          # syscall number for write
      mov $1, %rdi
                          # file descriptor for stdout
                          # pointer to the string
      mov $hello, %rsi
      mov $hello_len, %rdx # length of the string
      syscall
                          # invoke syscall
      # Exit
      mov $60, %rax
                          # syscall number for exit
      xor %rdi, %rdi
                          # exit status 0
                          # invoke syscall
      syscall
```







Syscalls

- Process Management
 - fork
 - exec
 - o clone
 - o wait
 - o kill
 - exit
 - o nice
 - getpid
 - 0 ..

- FS Management
 - open open
 - read
 - ∘ write
 - o close
 - \circ stat
 - o link
 - ∘ unlink
 - o ..


- Interprocess
 - > kill
 - o signal
 - o pipe
 - socket
 - o msgget
 - msgrcv
 - semgetsemop
 - o ..

- Memory Management
 - o brk
 - o mmap
 - munmap
 - . . .

- Similar to a library call
- Called by number, not by name of the function
- Operations requiring privileged access rights are executed in a safe environment
- Over 500 syscalls




Process Break





Step 1. Cloning



- Process A is the parent process
- Process B is the child process
- Both processes are exactly the same (stack, heap, code, file descriptors ...), except the PID, lock states and pending signals





Step 1. Cloning

Process A

Stack

Heap

Sockets

File Desc.

Step 1. Cloning

Process B


Stack

Heap

Sockets

File Desc.

- Process A is the parent process
- Process B is the child process
- Both processes are exactly the same (stack, heap, code, file descriptors ...), except the PID



 A new binary image is loaded from disk and completely overwrites address space of the original process

- Parent and child are separate processes
- They both continue executing code on the same instruction (in this example the if statement)

What If ...



- Parent and child are separate processes
- They both continue executing code on the same instruction (in this example the if statement)

What If ...

- You could define what is the child's entry point (what function should be executed after fork)
- Parent and child could share pieces of execution context (file descriptors, heap, stack, ...)



- Parent and child are separate processes
- They both continue executing code on the same instruction (in this example the **if** statement)

What If ...

- You could define what is the child's entry point (what function should be executed after fork)
- Parent and child could share pieces of execution context (file descriptors, heap, stack, ...)

clone()

 Leveraged by the pthread library to create new threads inside processes



Process Synchronization - Signals

```
sys_kill(pid_t pid, int sig)
#define SIGHUP
                                                         #define SIGKILL
                                                         #define SIGSEGV
proc_a:
                                                         #define SIGTERM
                                                         #define SIGSTOP
                                                                             19
int sig_flag = 0;
void my_handler(int s) {
                                                         task->sighand->
     sig_flag |= s;
                                                              ->action[sig - 1].sa.sa_handler
int main(void) {
. . .
     __signalhandler ret;
     ret = signal(SIGHUP, my_handler);
. . .
     if (signal_flag) {
```



Process Synchronization - Signals

```
sys_kill(pid_t pid, int sig)
#define SIGHUP
                                                          #define SIGKILL
                                                          #define SIGSEGV
proc_a:
                                                          #define SIGTERM
                                                          #define SIGSTOP
                                                                               19
int sig_flag = 0;
void my_handler(int s) {
                                                          task->sighand->
     sig_flag |= s;
                                                                ->action[sig - 1].sa.sa_handler
int main(void) {
. . .
                                                             There are 64 signals defined in Linux
     __signalhandler ret;
     ret = signal(SIGHUP, my_handler);
                                                             Signals are outdated,
                                                             use sigaction instead. Or ...
. . .
     if (signal_flag) {
```



Process Synchronization - Overview

Message Queues sysvipc msgget() msgsnd() System V Interprocess Communication msgrcv() msgctl() Shared Memory shmget() shmat() shmdt() shmctl() Semaphores semget() semop() semctl()

Sockets

- socket()
- bind()
- listen()
- accept()
- connect()
- send*()
- recv*()
- shutdown()
- close()

FIFOs

- mkfifo()
- mknod()

Signals

- kill()
- sigaction()
- signal()
- sigprocmask()
- sigpending()

Pipes


- pipe()
- pipe2()



Process Niceness

```
$ nice
0
$ strace nice
...
getpriority(PRIO_PROCESS, 0) = 20
...

$ ps ax -o pid,ni,cmd
    PID NI CMD
    1    0 /usr/lib/systemd/systemd --switched-root --system --deserialize=39 rhgb
    2    0 [kthreadd]
    3    0 [pool_workqueue_release]
    4 -20 [kworker/R-rcu_gp]
    5 -20 [kworker/R-sync_wq]
    6 -20 [kworker/R-slub_flushwq]
...
```



- Default value is 0
- Use renice to change
- Except nice values, there is also priority value for each process



Process States and Transitions

- (R) Running Process is being executed by the CPU
- **(S) Interruptible sleep** Process is waiting for an event, resource to be available or completion of a syscall. Process reacts to signals and can be killed
- **(D) Uninterruptible sleep** Process is sleeping in an uninterruptible wait, usually waiting for a block device IO. Does not react to signals and cannot be killed
- **(Z) Zombie** Process has finished its execution of code, but its parent process has not collected its exit code using the wait() syscall
- **(T) Traced/Stopped** Process is being traced or stopped.



Process From Kernel's Point of View



 $struct task_struct \rightarrow Task descriptor$

Task Descriptor/Task Structure

- One structure per user space or kernel thread
 - Every process has at least one thread
- Large C language structure
 - Contains all information about thread
 - o Scheduling information, memory mapping, signals, files, sockets, locks, paging tables, ...
- Macro current
 - Architecture specific implementation
 - Points to the task_struct that is being currently executed on that CPU (e.g. process called a syscall)
 - Does not have to be a user space process



struct task_struct

task_pid_nr(current)
task_tgid_nr(current)



struct task_struct - family

```
struct task_struct {
                                *parent;
                                                /* Parent process */
     struct task struct rcu
     struct list_head
                                children; /* List of children */
                                sibling; /* List of sibling */
     struct list_head
     struct list_head
                          tasks; /* Double linked list of all tasks */
     . . .
    Process PID: M
                                 Process PID:
                  Process PID: N
                                                                             Process PID: Z
```

struct task_struct - family

```
struct task_struct {
     struct task_struct __rcu
                           *parent; /* Parent process */
     struct list_head
                           children; /* List of children */
     struct list_head
                           sibling; /* List of sibling */
     struct list_head
                      tasks; /* Double linked list of all tasks */
#define for_each_process(p)
#define for_each_thread(p, t)
#define for_each_process_thread(p, t)
```



struct task_struct-state

```
struct task_struct {
     unsigned int __state;
#define TASK_RUNNING
                                     0x00000000
#define TASK INTERRUPTIBLE
                                     0x00000001
#define TASK_UNINTERRUPTIBLE
                                     0x00000002
#define EXIT DEAD
                                     0x00000010
#define EXIT_ZOMBIE
                                     0x00000020
#define EXIT TRACE
                                      (EXIT_ZOMBIE | EXIT_DEAD)
#define task_is_running(task)
                                      (READ_ONCE((task)->__state) == TASK_RUNNING)
```



struct task_struct - stacks

```
struct task_struct {
    ...
    void    *stack; /* kernel mode stack */
    ...
```

- Userspace threads have separate stacks for userspace and kernel mode
- Kernel threads have no userspace stack
- Userspace stacks are accessible through VMA structures
- Shadow stack Copy of user space stack
 - Created at entering syscall
 - When returning back to user space, return address to user space is compared with original stack



struct task_struct - affinity

- Bitmask of individual CPUs where the thread is allowed to run
- Individual threads can be bound, or denied to run on specific CPUs
- Can be modified using syscalls sched_getaffinity, sched_setaffinity, or user space tool taskset

```
$ taskset -p 1
pid 1's current affinity mask: ff
```




struct task_struct - scheduler

- task_struct.thread_info
 - \circ Per thread structure, contains a flag field, telling scheduler if thread should be preempted
 - Defined always as first item
- task_struct.thread
 - Architecture specific, on x86 contains CPU state when thread is preempted
 - Defined always last




Memory Space Descriptor mm_struct




Userspace mapping, NULL for kernel threads



Memory Space Descriptor mm_struct



Virtual Memory Space Descriptor vm_area_struct



Syscalls



Syscalls - Uname

```
$ uname -a
Linux fedora33-kw 6.8.11-200.fc39.x86_64 #1 SMP PREEMPT_DYNAMIC Sun May 26
20:05:41 UTC 2024 x86_64 GNU/Linux
```

Syscalls - Macros

- SYSCALL_METADATA Data for tracing events
- __SYSCALL_DEFINEx Complex machinery of macros and GCC extensions to create the syscall implementation



Syscalls - Entries

```
0 common read sys_read
1 common write sys_write
2 common open sys_open
```

```
$ sh ./scripts/syscalltbl.sh --abis common,64 arch/x86/entry/syscalls/s
    yscall_64.tbl arch/x86/include/generated/asm/syscalls_64.h
```

```
__SYSCALL(0, sys_read)
__SYSCALL(1, sys_write)
__SYSCALL(2, sys_open)
```

```
#define __SYSCALL(nr, sym) case nr: return __x64_##sym(regs);
```



Syscalls - Table

```
long x64_sys_call(const struct pt_regs *regs, unsigned int nr)
{
    switch (nr) {
        #include <asm/syscalls_64.h>
            default: return __x64_sys_ni_syscall(regs);
        }
};

__SYSCALL(0, sys_read)
    __SYSCALL(1, sys_write)
    __SYSCALL(2, sys_open)
```



Copying data to and from user space

Copy simple values:

- get_user(x, ptr); // Get a simple variable from user space.
- put_user(x, ptr); // Write a simple value into user space.
 - o x Variable to store result
 - o ptr Source/Destination address, in user space.

Copy data:

- copy_from_user(void *to, const void __user *from, unsigned long n);
- copy_to_user(void __user *to, const void *from, unsigned long n);



Process Scheduler

Scheduler

- Divide CPU resources between competing consumers (user/kernel threads)
- Smallest scheduled unit is a thread (every process has at least one thread)
- Thread state machine is defined using flags
- Threads being executed or are ready to be executed are stored in a structure named
 runqueue
- Sleeping threads are stored in waitqueue
- Each CPU has its own runqueues
- Waitqueue is created by device drivers and the kernel, there can be many wait queues



Context Switch / Process Swap

Threads leave the CPU in one of two ways:

- Voluntary
 - Thread is waiting for an IO operation to finish
 - Thread is waiting for a lock to be opened
 - Thread decides to sleep
- Involuntary
 - Scheduling: When the CPU scheduler decides to switch to a different thread based on scheduling policies (e.g. processes exceeded its scheduled allocation of CPU time)
 - Preemption: When a higher-priority thread becomes ready to run and preempts the currently executing thread.



Context Switch / Process Swap

- Architecture specific
- Expensive operation
 - Saving CPU state of current thread (previous)
 - Installing MM settings of the new (next) thread
 - Restoring CPU state of the new (next) thread
 - context_switch(...)

Scheduler Policies

- Linux scheduler consists of several scheduling policies
- Scheduling policy == scheduling algorithm
- Every thread in the system is associated with only one policy
- Current scheduling policies
 - SCHED_DEADLINE
 - SCHED_FIFO, SCHED_RR
 - SCHED_NORMAL, SCHED_BATCH, SCHED_IDLE



Scheduling Classes

- Abstraction classes that hold the individual scheduling policies
- New classes can be added and removed to source code depending on need
- Each scheduling class has a different model how to select eligible tasks/threads, each scheduling class maintains its own runqueue

```
struct sched_class {
...
    void (*enqueue_task) (struct rq *rq, struct task_struct *p, int flags);
    void (*dequeue_task) (struct rq *rq, struct task_struct *p, int flags);
...
    struct task_struct *(*pick_next_task)(struct rq *rq);
...
    void (*task_tick)(struct rq *rq, struct task_struct *p, int queued);
...
}
```



Stop Scheduler Class

- Does not have a policy
- Highest priority
- Can preempt everything and is preempted by nothing
- Available only on SPM
- One kernel thread per CPU
 - o "migration/N"
- Used by task migration, CPU Hotplug, RCUs, ftrace, kernel live patching



(Early) Deadline Scheduler Class

- Policy SCHED_DEADLINE
- The task with the earliest deadline will be served first.
- User has to set 3 parameters
 - Period activation pattern of the real time task
 - Runtime amount of CPU time that the application needs
 - Deadline maximum time in which the result must be delivered
- Used for periodic real time tasks e.g. multimedia, industrial control



Real Time Scheduler Class

- Used for short latency sensitive tasks
- Two policies
- SCHED_FIFO
 - AKA POSIX scheduler
 - o Runqueue is a FIFO pipe
 - Thread will run until it voluntary yields the CPU
 - Real time aggressive
- SCHED_RR
 - o 100ms time slice by default
 - Round Robin scheduler
 - o Realtime moderately aggressive



EEVDF - Earliest Eligible Virtual Deadline First

- Most common used scheduler, used for the rest of the all tasks in the system
- Superseded CFS "Completely Fair Scheduler" scheduler by Ingo Molnar in v6.6 from 2007
- Described in this 1995 paper by Ion Stoica and Hussein Abdel-Wahab
- Scheduling policies
 - SCHED_NORMAL Normal Unix tasks, default scheduler
 - SCHED_BATCH Low priority, non interactive jobs
 - SCHED_IDLE Nothing else is runnable on a CPU



EEVDF - Earliest Eligible Virtual Deadline First

- Available CPU time equally between all of the runnable tasks in the system (assuming all have the same priority)
- Uses two factors to determine what processes to run
 - "Lag" the difference between the time that process should have gotten and how much it actually got, is used to calculate the eligible time
 - "Virtual Deadline" earliest time by which a process should have received its due CPU time
- EEVDF it will run the process with the earliest virtual deadline first
- Implemented with red-black trees



The Extensible Scheduler

- Scheduling policy SCHED_EXT
- Introduced recently in Jan 2023
- Idea of "plugable schedulers"
- Not really a scheduler itself, but a framework
- Uses eBPF technology
 - Runtime load schedulers from userspace
 - Without need to recompile the kernel
 - Allows safe experimentation
 - Library of schedulers for niche applications (e.g. service, specific game, ...)



Scheduler Code

- schedule() → __schedule() → __pick_next_task()
- Classes are ordered by the task priority they cover, classes with higher priority are being queried first
- __pick_next_class returns a pointer to the task_struct it self which will be executed



Thread Scheduling

- Thread state machine is defined using flags
 - task_struct.thread_info.flas |= TIF_NEED_RESCHED
 - set_tsk_need_resched(struct task_struct *tsk)

- Who is calling the scheduler?
 - Executed in context of current process
 - Return from syscall
 - Return from interrupt



Thank you!

Questions?

