Filesystem and Storage Subsystems



Agenda

Overview


- Introduction to storage and block devices
- Virtual File system
- The Block I/O Layer
- Process Address Space
- Page cache and Page Writeback
- Case study ToyFS filesystem






What is a File?





What is a Filesystem?





Introduction



What are block devices?

- Storage devices are accessible through sector/block addresses
 - · HDDs, SSDs, DVD/Blu-Ray etc
- Using specific communication protocols to access
 - · IDE, SCSI, SATA, SAS, etc



The sector as the fundamental unit

- Storage's smallest addressable unit
- Come by many names
 - Sectors, physical block size, I/O blocks...
- May come in different sizes depending on the media
 - 512 Bytes
 - 4096 Bytes 512e and 4KN
 - · 2KiB 64Kib (Blu-Rays)



Logical Blocks

- Aggregation of one or more consecutive physical sectors
- Smallest "logical" addressable unit for logical volumes
 - RAID arrays
 - LVMs volumes (depending on volume type)
 - other volume managers.



Filesystem Blocks

- Aggregation of one or more consecutive physical blocks, depending on the underlying media
- Smallest "logical" addressable unit for:
 - Filesystems
 - User applications




Files (in Unix context)

- A container of data
 - · An "unstructured" array of bytes, nothing more, nothing less
 - Stored on top of filesystem blocks (for disk-based filesystems)
- Abstraction used by applications and users to store and retrieve data



"Bringing them all together..."



I/O operations vs File Operations

- ► I/O operations (IOPS)
 - · Storage Unit Commands
 - 95% READ and WRITE

- File Operations (**OPS**)
 - File-related operations
 - open(), close()
 - read(), write()
 - stat(), lseek()

Extra important details...


- Physically, any write other than a sector IS NOT ATOMIC
- ► The Read-Modify-Write curse
- Torn writes
- Storages are usually capable of reading and writing sectors in batches



Object Oriented recap

- OOP is not a programming language, it is a programming paradigm
- Basically the whole kernel is objected oriented
- C doesn't have OOP-specific support, so we need to use some different techniques.





Virtual File System

The most important subsystem



The VFS responsibility

- All file and filesystem-related interfaces available to userspace and other kernel subsystems.
- Virtually everything is interconnected by the VFS
 - You read and write from/to network sockets using VFS
- Abstracts the internal operations of all filesystems
- Most system calls are initially handled by the VFS.
- Together with the block layer, we have all necessary abstractions for user-space to access data in any media using the same generic system calls




The common file model

- VFS defines "generic" view for files, filesystems, etc.
- This ensures that accessing any filesystem object can be done via a generic interface without the need to understand the details of each specific filesystem.
- Each filesystem though must abstract their internal implementation to the VFS using such model.



The journey of a write() syscall



Disclaimer: This is not 100% accurate...

Main VFS Abstractions



Superblock

Represents a **specific mounted** filesystem



Inode

Descriptor containing

metadata details related to a

specific file.



Directory Entries

A **single component** in a path (not a directory).



File

An in-memory representation of an **opened file**





Operations

- Each object provides a "structure" providing a set of operations for that specific object
- Each filesystem will populate this with their own operations
- Not all operations are mandatory and the VFS provide some generic ones if the filesystem doesn't need any custom behavior
- Yes you can call these operations "methods"

VFS data structures definitions

Object	Operations	Location
super_block	super_operations	include/linux/fs.h
inode	inode_operations	include/linux/fs.h
dentry	dentry_operations	include/linux/dcache.h
file	file_operations	include/linux/fs.h

Other important structures

- file_system_type (include/linux/fs.h)
- mount (fs/mount.h)
- vfsmount (include/linux/fs.h)
- files_struct (include/linux/fs.h)
- fs_struct (include/linux/fs.h)
- mnt_namespace (include/linux/fs.h)

The Dentry Cache

- dentry object describes components in a path name
- Pathname lookups are very expensive, so we cache it.
- dentries have no on-disk correspondent, even on native Unix filesystems.
- Even invalid lookups are cached.
- Dentry cache also provides a front end for the inode cache





A quick look into the block I/O layer



Buffers


- Every block read from disk storage, is cached in memory for some time.
- These blocks are stored in "buffers"
- buffer_head struct is used to cache blocks

struct bio and bvec_iter

- Bio the basic container for I/O within the kernel
- Represents every "in-flight" IO operation
- ► A bio describe a SINGLE contiguous storage location.
- Each bio is divided in segments chunks of contiguous memory.



struct bio and bvec_iter#2



Request queues


- Each block device keeps its own request queue
- Higher level systems add requests to these queues
- The device driver grab such requests and submit them to the hardware



IO Schedulers

- Do not confuse with CPU schedulers
- Decide the order and the time requests are dispatched to the block device
- Most of the time, IO schedulers aim to reduce disk seeks
- Linux provides different scheduling algorithms





"Free Memory is wasted memory."

The Page cache and writeback mechanism



Linux page cache

- Introduced initially in SysVr4 meant to cache only FS data
- Linux page cache aims to cache any page-based object
- The goal is to minimize disk I/O
 - · milliseconds vs nanoseconds
- Temporal locality
 - · Once accessed, data is likely to be accessed again



Linux page cache #2

- Physical pages in RAM related to physical blocks on disk
- Page cache is dynamic
 - Can grow and consume any free memory
 - Can shrink and relieve memory pressure if memory is low



Page cache based WRITES

- Page cache writes can be implemented in different ways
 - No-write system does not cache write operations
 - Write-through Write operations update both cache and disk
 - Write-back Write goes to the cache only (Linux does this)



Page cache based READS

- Kernel first checks if the requested data is in the page cache
 - If we do, we have a **cache hit** and we don't need to go to the disk
- If not, we have a cache miss.
 - The kernel will schedule a block I/O operation to request the data off disk
- Once the data is read, it will now be added to the cache



Page cache based WRITES #2

- write operations write data to the page cache only
- Pages in the cache are marked dirty by the write operation
- After a determined amount of time and some rules, the pages are written back to disk.
- After return, a write() call does not guarantee the data is on disk
- Applications are responsible for their data integrity, not the kernel.
 - sync(), fsync(), fdatasync()
- System performance is the goal here



Cache eviction

- If memory is running low (or specified limits are being hit), the kernel needs to shrink the page cache.
- Which blocks should be uncached?
- What if there are no 'clean pages' in the page cache?

Cache eviction #2

- Linux use a modified LRU, consisting of two lists:
- Active and Inactive list
- Active list contain "hot" pages and can't be evicted
- Pages in the Inactive list are available for cache eviction
- Only when a page is accessed while in the inactive list, it can be "promoted" to the active list.
- ▶ Both lists are balanced. If the active list becomes larger than the inactive one, items are moved from the active to the inactive list



The address_space object

- A page in the page cache, may contain multiple non-contiguous physical disk blocks.
 - As files need not to be contiguous on disk, this works well.
- Linux uses the address_space object to manage entries in the page cache and page I/O operations.
 - By not tying it to specific VFS objects, like the inode, SB, we enable the page cache to be a generic cache, not usable only by filesystems.



The address_space object #2

- A file mapped in memory, will have a single address_space struct representing it.
 - Opposite of VMAs, where we can have several VMAs pointing to the same file.
 - It may have many virtual addresses, but it exists only once in physical memory
- Show me some code



address_space operations

- Yes, address_space also have different behaviors depending on the underlying user.
- The underlying user may be:
 - Filesystems, block devices, the buffer_head cache, swap subsystem.

Flusher Threads

- All storage writes are handled via the page cache
 - We will talk about DIO next.
- All writeback is deferred to the "flusher threads"
- If data in the page cache is dirty
 - · i.e. newer than their respective disk locations.
- The pages will be written back to disk once some conditions are met.
- The writeback is handled by flusher threads, which are kworker threads started on demand as a per-device basis



Flusher Threads #2

- So, when does writeback occurs?
 - · Free memory is smaller than a specific threshold
 - Dirty data grows older
 - The user process forces the writeback to disk
 - sync() syscalls family

Disclaimer!!

FILESYSTEMS DON'T CARE ABOUT USER DATA

- It is not uncommon for users and developers to assume once a write() returns, the data is written on disk
- ► Again, it is user's (or application's) responsibility to ensure data is safe



Direct IO


- From userspace, we can bypass the page cache by using Direct IO
 - All reads and writes goes from/to user space memory direct to/from disk using DMA.
- This has a big potential to increase performance (and power usage)
 - But as anything in computer world, there is a trade-off
- With DIO applications have more control over IO
- CPU usage is reduced
- IO must be aligned with the device's sector sizes



Going further

- Journalling
- COW filesystems
- Dynamically allocation of metadata
- Extents







Case study: The Ext2 Filesystem



Ext2 Disk Layout




Ext2 Disk Layout #2



On-disk vs In-memory structures

Object	On-disk	In-memory
Superblock	ext2_super_block	ext2_sb_info
Group Descriptor Table	ext2_group_desc	ext2_group_desc
Block bitmap	Raw format	Raw format
Inode bitmap	Raw format	Raw format
Inode table	Array of inodes	Raw format
Data blocks	file_operations	include/linux/fs.h

On-memory and on-disk structures



Memory

Block Device

Initializing an Ext2 Filesystem

- As virtually any other filesystem it is initialized in userspace via specific tools (mkfs and friends)
- Goals:
 - parse config options
 - · analyze the disk
 - create and initialize all metadata needed so that the kernel can properly mount and operate the filesystem

Ext2 operations (aka methods)

- super_operations -> ext2_sops
- inode_operations ->
 - ext2_file_inode_operations
 - ext2_dir_operations
 - ext2_special_operations
- file_operations -> ext2_file_operations
- vm_operations_struct -> ext2_dax_vm_ops (no ops defined for non-dax)
- address_space_operations -> ext2_aops (ext2_dax_aops)



Metadata management

- File layout on disk may differ from the user perspective
 - File data can be scattered everywhere on disk
 - Even though users just see a contiguous array of bytes
- Files may have holes in them (Sparse files)
- Space management attempts to address 2 main problems
 - Space fragmentation big deal for spindles
 - Time efficiency

Inode creation

- ext2_new_inode() allocate an ext2 disk inode and returns the address of the corresponding VFS inode object
- file vs directory allocation
- Update block group metadata
- Update superblock
- Initialize inode object
- Initialize quotas, acls, system security
- Pre-fetch the on-disk inode block where the new inode will be written.



Inode deletion

- Homework
 - · Go and figure out what ext2_free_inode() does


Data Addressing

- Files consists of blocks stored within block groups
- We can refer to them either as:
 - Their relative position inside the file (File block num)
 - Their position within the volume/partition (Logical block num)

Data Addressing #2

- Retrieval of a file's logical block number, is a two-step process:
 - 1 Derive from the file offset, the block index containing such offset
 - 2- Translate the file block number to the corresponding logical block number
- Ext2 uses a simple data blocks management named Indirect blocks
- The ext2_inode contains an array of 15 block pointers

Data Addressing #3



Block allocation

- ext2_get_block() and ext2_new_blocks()
 - · Initially, attempts to find if the block already exists
 - If not, allocate a new one (or several ones)
- The allocator tries to reduce fragmentation, by allocating blocks as close as possible to the last already allocated block.
- The FS also does pre-allocation, by anticipating next writes beyond the first block requested.
- Ext2 allocator is a bit smarter now, and it tries to allocate blocks in batches



Data deletion

- Data blocks must be reclaimed once a file is deleted or truncated
- We can also 'leak' data blocks the same way we leak memory
- Homework
 - Go read what ext2_truncate_blocks() and ext2_free_blocks() do



Extra Mile: ToyFS




Overview

- Simple filesystem inspired on Steve Pate's UXFS
- Fixed 512 blocks of 2048 bytes (total space 1MiB)
- Implements fundamental filesystem operations


On-disk and In-memory structures


Object	Block	On-disk	In-memory
Superblock	# O	tfs_dsb	tfs_fs_info
Inode list	#1	tfs_dinode	tfs_inode_info
Block bitmap	#2	Raw format	Raw format
Data blocks	#3 to #511	User data	User data
Directory entry	N/A	tfs_dentry	tfs_dentry

Disk layout



ToyFS data addressing





Thank you

Red Hat is the world's leading provider of enterprise open source software solutions. Award-winning support, training, and consulting services make Red Hat a trusted adviser to the Fortune 500.

- in linkedin.com/company/red-hat
- youtube.com/user/RedHatVideos
- facebook.com/redhatinc
- X twitter.com/RedHat

